

WILDPEAK A/T4W



Rim Diameter	Item Number	Tire Size	Load ID	Ply Rating	Service Desc.	Sidewall Stamp	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revs Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load Single / Dual (lbs)	Max Pressure (psi cold)"	U.T.Q.G.
15"	28844151	225/75R15	XL	--	106T	Standard	6.0 - 7.5	6	28.3	8.8	747	13	35.1	2094	50	660-B-B
	28844108	235/75R15	XL	--	109T	Standard	6.0 - 8.0	6.5	28.9	9.3	734	13	38.8	2271	50	660-B-B
	28847272	LT215/75R15	D	8	106/103R	Standard	5.5 - 7.0	6	27.7	8.6	752	16	37.5	2095/1930	65	--
	28847202	LT235/75R15	E	10	116/113R	HD	6.0 - 7.0	6.5	28.8	9.3	724	17	40.5	2755/2535	80	--
	28840112	30x9.5R15LT	C	6	104S	Standard	6.5 - 8.5	7.5	30	9.8	705	17	43.2	1985	50	--
	28840114	31x10.5R15LT	C	6	109S	Standard	7.0 - 9.0	8.5	31.1	11	681	17	50.3	2270	50	--
	28847115	32x11.5R15LT	C	6	113R	Standard	8.0 - 10.0	9	32.1	11.9	660	18	55.6	2535	50	--
	28847116	33x12.5R15LT	C	6	108R	Standard	8.5 - 11.0	10	33.1	13.1	642	19	59.8	2205	35	--
	28847117	35x12.5R15LT	C	6	113R	Standard	Available Q3 2024									
16"	28847745	225/75R16C	E	10	121/120R	Standard	6.0 - 7.0	6	29.2	8.8	713	16	41.2	3195/3085	83	--
	28847033	235/65R16C	E	10	121/119R	Standard	6.5 - 7.5	7	28.1	9.4	745	17	42.2	3195/3000	83	--
	28844109	235/70R16	XL	--	109T	Standard	6.0 - 8.0	7	29	9.4	729	13	38.2	2271	50	660-A-B
	28844146	245/75R16	XL	--	115T	Standard	6.5 - 8.0	7	30.5	9.8	694	13	41.2	2679	50	660-A-B
	28844657	255/70R16	XL	--	115T	Standard	6.5 - 8.5	7.5	30.1	10.2	703	13	44	2679	50	660-A-B
	28844667	265/70R16	SL	--	112T	Standard	7.0 - 9.0	8	30.6	10.7	692	14	45.6	2469	51	660-A-B
	28844301	265/75R16	SL	--	116T	Standard	7.0 - 9.0	7.5	31.7	10.5	671	14	45.1	2756	51	660-A-B
	28847017	LT215/85R16	E	10	115/112R	HD	5.5 - 7.0	6	30.4	8.7	686	16	43.1	2680/2470	80	--
	28840119	LT225/75R16	E	10	115/112S	HD	6.0 - 7.0	6	29.2	8.8	713	16	41.6	2680/2470	80	--
	28840994	LT235/85R16	E	10	120/116S	HD	6.0 - 7.5	6.5	31.7	9.6	658	17	48.5	3042/2778	80	--
	28840628	LT245/75R16	E	10	120/116S	HD	6.5 - 8.0	7	30.3	9.8	690	17	47.6	3042/2778	80	--
	28840034	LT255/85R16	C	6	112/109S	DURASPEC	6.5 - 8.0	7	33.1	10.3	633	17	58.4	2470/2270	50	--
	28840639	LT265/75R16	E	10	123/120S	HD	7.0 - 8.0	7.5	31.9	10.8	655	17	53	3415/3085	80	--

WILDPEAK A/T4W



Rim Diameter	Item Number	Tire Size	Load ID	Ply Rating	Service Desc.	Sidewall Stamp	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revs Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load Single / Dual (lbs)	Max Pressure (psi cold)"	U.T.Q.G.
17"	28847611	LT285/75R16	E	10	126/123R	HD, DURASPEC	7.5 - 9.0	8	33.1	11.6	633	18	62.6	3750/3415	80	--
	28847641	LT305/70R16	E	10	124/121R	HD	8.0 - 9.5	9	32.8	12.6	637	18	63.1	3525/3195	65	--
	28847124	LT315/75R16	E	10	127/124R	HD, DURASPEC	8.0 - 11.0	8.5	34.6	12.7	605	19	76.6	3860/3525	65	--
	28844913	P285/70R17	SL	--	116T	Standard	7.5 - 9.5	8.5	32.8	11.5	647	14	53.4	2756	51	660-A-B
	28844782	215/65R17	SL	--	99T	Standard	6.0 - 7.5	6.5	28	8.7	756	13	32.6	1709	51	660-B-B
	28844775	225/65R17	XL	--	106T	Standard	6.0 - 8.0	6.5	28.5	9	743	13	34.8	2094	50	660-B-B
	28841790	235/65R17	SL	--	104H	Standard	6.5 - 8.5	7	29.1	9.4	731	13	38.2	1984	51	660-A-A
	28844737	235/75R17	SL	--	109T	Standard	6.0 - 8.0	6.5	30.9	9.3	683	13	40.8	2271	51	660-A-B
	28844768	245/65R17	XL	--	111T	Standard	7.0 - 8.5	7	29.5	9.8	719	13	41.9	2403	50	660-A-B
	28844747	245/70R17	XL	--	114T	Standard	6.5 - 8.0	7	30.6	9.8	691	13	40.9	2601	50	660-A-B
	28844713	255/65R17	XL	--	114T	Standard	7.0 - 9.0	7.5	30.1	10.2	708	13	42.4	2601	50	660-A-B
	28844769	255/70R17	SL	--	112T	Standard	6.5 - 8.5	7.5	31.1	10.2	679	13	43	2469	51	660-A-B
	28844721	265/65R17	XL	--	116T	Standard	7.5 - 9.5	8	30.6	10.7	697	13	45.3	2756	50	660-A-B
	28844300	265/70R17	SL	--	115T	Standard	7.0 - 9.0	8	31.7	10.7	668	14	47.6	2679	51	660-A-B
	28847616	LT235/80R17	E	10	120/117R	HD	6.0 - 7.5	6.5	31.8	9.4	655	17	47.1	3085/2835	80	--
	28840718	LT245/70R17	E	10	119/116S	HD	6.5 - 8.0	7	30.8	9.8	676	17	49.1	3000/2755	80	--
	28840601	LT245/75R17	E	10	121/118S	HD	6.5 - 7.5	7	31.8	9.8	657	17	49.8	3195/2910	80	--
	28840338	LT255/80R17	E	10	123/120S	HD, DURASPEC	6.5 - 8.5	7	33	10.3	632	17	58.1	3415/3085	80	--
	28840712	LT265/70R17	E	10	123/120S	HD	7.0 - 8.5	8	31.86	11.2	625	17	53.2	3415/3085	80	--
	28840722	LT275/70R17	C	6	114/110S	Standard	7.0 - 8.5	8	32.2	11	648	18	58.1	2600/2335	50	--
	28847543	LT285/70R17	C	6	116/113R	DURASPEC	7.5 - 9.0	8.5	33	11.5	632	18	65.4	2755/2535	50	--

WILDPEAK A/T4W



Rim Diameter	Item Number	Tire Size	Load ID	Ply Rating	Service Desc.	Sidewall Stamp	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revs Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load Single / Dual (lbs)	Max Pressure (psi cold)"	U.T.Q.G.
	28840612	LT285/70R17	E	10	126/123S	HD, DURASPEC	7.5 - 9.0	8.5	33	11.5	632	18	65.4	3750/3415	80	--
	28847839	LT285/75R17	C	6	117/114R	DURASPEC	7.5 - 9.5	8	34.1	11.6	613	18	67.9	2835/2600	50	--
	28840588	LT285/75R17	E	10	128/125S	HD, DURASPEC	7.5 - 9.5	8	34.1	11.6	613	18	67.4	3970/3640	80	--
	28840144	LT315/70R17	C	6	113/110S	DURASPEC	8.0 - 11.0	9.5	34.7	13.1	602	19	75.7	2535/2335	35	--
	28847336	35x11.5R17LT	C	6	118R	DURASPEC	7.5 - 10.0	9	35	11.9	604	18	68.5	2910	50	--
	28847282	35x12.5R17LT	E	10	125R	HD, DURASPEC	8.5 - 11.0	10	35.1	12.8	602	19	78.2	3640	65	--
	28847341	37x12.5R17LT	E	10	128R	HD, DURASPEC	8.5 - 11.0	10	37	13.1	573	19	78.3	3970	65	--
18"	28844841	255/70R18	SL	--	113T	Standard	6.5 - 8.5	7.5	32.1	10.2	658	13	44.6	2535	51	660-A-B
	28844854	265/60R18	XL	--	114T	Standard	7.5 - 9.5	8	30.5	10.7	696	13	42.8	2601	50	660-A-B
	28844823	265/65R18	SL	--	114T	Standard	7.5 - 9.5	8	31.5	10.7	675	13	46.8	2601	51	660-A-B
	28844809	265/70R18	SL	--	116T	Standard	7.0 - 9.0	8	32.6	10.7	646	14	50.2	2756	51	660-A-B
	28844901	275/65R18	SL	--	116T	Standard	7.5 - 9.5	8	32.1	11	663	14	48.6	2756	51	660-A-B
	28844888	285/65R18	SL	--	116T	Standard	8.0 - 10.0	8.5	32.6	11.5	655	14	51.4	2756	51	660-A-B
	28847324	LT265/65R18	E	10	122/119R	HD	7.5 - 9.5	8	31.7	10.7	661	17	54.5	3305/3000	80	--
	28840233	LT265/70R18	E	10	124/121S	HD	7.0 - 9.0	8	33.4	11.2	624	17	57.2	3525/3195	80	--
	28840803	LT275/65R18	E	10	123/120S	HD	7.5 - 9.0	8	32.2	10.9	649	18	57.1	3415/3085	80	--
	28840886	LT275/70R18	E	10	125/122S	HD	7.0 - 9.0	8	33.43	11.2	624	18	60.3	3640/3305	80	--
	28840827	LT285/65R18	E	10	125/122S	HD	8.0 - 10.0	8.5	32.6	11.7	642	18	60.3	3640/3305	80	--
	28840692	LT285/70R18	C	6	117/114S	DURASPEC	7.5 - 9.5	8.5	34	11.5	614	18	68	2835/2600	50	--
	28840115	LT285/75R18	E	10	129/126S	HD, DURASPEC	7.5 - 9.5	8	35	11.6	598	18	67.2	4080/3750	80	--

WILDPEAK A/T4W



Rim Diameter	Item Number	Tire Size	Load ID	Ply Rating	Service Desc.	Sidewall Stamp	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revs Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load Single / Dual (lbs)	Max Pressure (psi cold)"	U.T.Q.G.
	28847589	LT295/70R18	E	10	129/126R	HD, DURASPEC	7.5 - 10.0	8.5	34.3	12.2	609	18	69.2	4080/3750	80	--
	28847335	LT305/65R18	F	12	128/125R	HD	8.5 - 11.0	9	33.8	12.2	620	18	67	3970/3640	80	--
	28844599	LT325/65R18	D	8	121/118T	DURASPEC	9.0 - 12.0	9.5	34.6	13.2	605	19	75.4	3195/2910	50	--
	28840266	35x11.5R18LT	C	6	117S	Standard	7.5 - 10.0	9	34.9	11.9	604	18	62.6	2835	50	--
	28847580	35x12.5R18LT	F	12	128R	HD, DURASPEC	8.5 - 11.0	10	35.1	13	601	19	73.9	3970	80	--
20"	28844456	265/60R20	SL	--	112T	Standard	7.5 - 9.5	8	32.5	10.7	650	13	47.2	2469	51	660-A-B
	28844021	275/55R20	XL	--	117T	Standard	7.5 - 9.5	8.5	31.9	11.2	662	13	48.3	2833	50	660-A-B
	28844003	275/60R20	SL	--	115T	Standard	7.5 - 9.5	8	33	11	642	13	50.7	2679	51	660-A-B
	28844097	285/55R20	SL	--	114T	Standard	8.0 - 10.0	9	32.4	11.7	654	13	51.3	2601	51	660-A-B
	28844030	305/50R20	XL	--	120T	Standard	8.5 - 11.0	9.5	32	12.4	659	13	57.5	3086	50	660-A-B
	28844386	305/55R20	SL	--	116T	Standard	8.5 - 11.0	9.5	33.2	12.4	637	13	57.5	2756	51	660-A-B
	28840128	LT265/60R20	E	10	121/118S	HD	7.5 - 9.5	8	32.5	10.7	640	17	58	3195/2910	80	--
	28840008	LT275/55R20	D	8	115/112S	Standard	7.5 - 9.5	8.5	32.1	11.2	648	18	57.7	2680/2470	65	--
	28840009	LT275/60R20	D	8	119/116S	Standard	7.5 - 9.5	8	33.1	10.9	628	18	59.5	3000/2755	65	--
	28840025	LT275/65R20	E	10	126/123S	HD	7.5 - 9.5	8	34.1	10.8	611	18	65.3	3750/3415	80	--
	28844121	LT285/55R20	E	10	122/119T	HD	8.0 - 10.0	9	32.6	11.7	639	18	60.4	3305/3000	80	--
	28847593	LT285/60R20	E	10	125/122R	HD	8.0 - 10.0	8.5	33.6	11.4	619	18	63.3	3640/3305	80	--
	28847594	LT285/65R20	E	10	127/124R	HD	8.0 - 10.0	8.5	34.8	11.5	600	18	67.4	3860/3525	80	--
	28844595	LT295/55R20	E	10	123/120T	HD	8.0 - 10.0	9.5	33	12.2	632	18	64.6	3415/3085	80	--
	28847596	LT295/60R20	E	10	126/123R	HD	8.0 - 10.0	8.5	34	11.7	613	18	66.6	3750/3415	80	--
	28840597	LT295/65R20	E	10	129/126S	HD	8.0 - 10.0	8.5	35.4	11.8	591	18	72.1	4080/3750	80	--

WILDPEAK A/T4W



Rim Diameter	Item Number	Tire Size	Load ID	Ply Rating	Service Desc.	Sidewall Stamp	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revs Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load Single / Dual (lbs)	Max Pressure (psi cold)"	U.T.Q.G.
	28840385	LT305/55R20	F	12	125/122S	HD	8.5 - 11.0	9.5	33.5	12.4	623	18	68.1	3640/3305	80	--
	28840125	LT325/60R20	E	10	126/123S	HD	9.0 - 12.0	9.5	35.5	13.1	588	19	76.1	3750/3415	65	--
	28840598	33x12.5R20LT	F	12	119S	HD	8.5 - 11.0	10	32.9	12.6	635	19	72.2	3000	80	--
	28840310	35x11.5R20LT	D	8	120S	Standard	8.0 - 10.5	9	35	11.5	599	18	64.5	3085	65	--
	28847307	35x12.5R20LT	F	12	125R	HD, DURASPEC	8.5 - 11.0	10	35.1	13.1	598	19	79.8	3640	80	--
	28847550	37x12.5R20LT	E	10	126R	HD	8.5 - 11.0	10	37	13	569	19	-	3750	65	--
22"	28844219	285/45R22	XL	--	114T	Standard	9.0 - 10.5	9.5	32.1	11.2	648	13	50.7	2601	50	660-A-B
	28840215	305/45R22	XL	--	118S	Standard	9.5 - 11.5	10	32.8	11.9	635	13	54.9	2910	50	660-A-B
	28847157	LT285/55R22	E	10	124/121R	HD	8.0 - 10.0	9	34.6	11.7	600	18	65.7	3525/3195	80	--
	28847557	LT325/50R22	F	12	127R	HD	9.0 - 12.0	10	35	13.1	593	19	76.5	3860	80	--
	28847504	35x12.5R22LT	E	10	117R	HD	8.5 - 11.0	10	34.9	12.6	598	19	73.9	2835	65	--
	28847632	37x12.5R22LT	F	12	127R	HD	9.0 - 11.5	10	37	13.1	566	19	79.4	3860	80	--